

# RealValidExam



## Try before you buy

Download a free sample of any of our exam questions and answers

- ✓ 24/7 customer support, Secure shopping site
- ✓ Free One year updates to match real exam scenarios
- ✓ If you failed your exam after buying our products we will refund the full amount back to you.

## Choose an exam to sample

Select a vendor... ▼

Select an exam... ▼

Your email address

 [Download Now](#)



### QUALITY AND VALUE

RealValidExam Practice Exams are written to the highest standards of technical accuracy, using only certified subject matter experts and published authors for development - no all dumps.



### TESTED AND APPROVED

We are committed to the process of vendor and third party approvals. We believe professionals and executives alike deserve the confidence of quality coverage these authorizations provide. anEdison



### EASY TO PASS

If you prepare for the exams using our RealValidExam testing engine, It is easy to succeed for all certifications in the first attempt. You don't have to deal with all dumps or any free torrent / rapidshare all stuff.



### TRY BEFORE BUY

RealValidExam offers free demo of each product. You can check out the interface, question quality and usability of our practice exams before you decide to buy.

<http://www.realvalidexam.com>

100% real and valid exam dumps can ensure you pass at the first attempt

**Exam** : **920-271**

**Title** : Nortel WLAN 2300 RIs.7.0  
implementation and  
Management

**Vendor** : Nortel

**Version** : DEMO

**NO.1** An access point generates a 4 W signal; it is equipped with a cable that has a loss of 3 dB and an antenna with a gain of 10 dB. What is the power radiated to the air?

- A. 40 W
- B. 2 W
- C. 20 W
- D. 10 W

**Answer:** C

**NO.2** A VPN using IPSec has been chosen as a security measure in a customer's WLAN deployment. What additional security measures should you take for this deployment?

- A. allow SSID broadcasts in the network
- B. disable the encapsulating security payload (ESP) protocol on the network
- C. require the client to authenticate using the WLAN firewall or security switch to start an IPSec session
- D. ensure a secure IPSec connection, applying a different set of rules to the server so the client does not know the server settings

**Answer:** C

**NO.3** Information gathered in Wireless Management System (WMS) can be exported in the form of reports. Which format is the default format for exported reports in WMS?

- A. XML
- B. PDF
- C. HTML
- D. CGML

**Answer:** C

**NO.4** Which parameter does not affect the number of RF fingerprints that can be captured by the Nortel Wireless Location Engine?

- A. size of the locales
- B. size of the building
- C. precision of tracking required
- D. number of wireless access points

**Answer:** D

**NO.5 DRAG DROP**

Click on the Task button.

The Location Tracking services within the WLAN 2300 require a deployment planning process before implementation.

Assume a new deployment. Place the deployment planning stages in the correct sequential order. (Stage 1 has already been placed.)

Place the deployment planning stages in the correct sequential order. (Stage 1 has already been placed.)

Set local boundaries	Map the space
Plan fingerprints	Stage 2
Plan AP placement	Stage 3
Determine business needs	Stage 4
	Stage 5

**Answer:**

Place the deployment planning stages in the correct sequential order. (Stage 1 has already been placed.)

Set local boundaries	Map the space
Plan fingerprints	Determine business needs
Plan AP placement	Set local boundaries
Determine business needs	Plan AP placement
	Plan fingerprints